



U.S. Department of Energy
Office of Civilian Radioactive Waste Management



Waste Form Degradation Alternative Analysis (Water Balance Model)

Presented to:
Nuclear Waste Technical Review Board

Presented by:
Pat Brady
Yifeng Wang
Sandia National Laboratories

January 16, 2008
Las Vegas, NV

Outline

- **Objectives of Performance Margin Analysis (PMA)**
- **Total system performance assessment (TSPA)
treatment of water fluxes**
- **PMA treatment of water fluxes**
- **Results**



Performance Margin Analysis

- Quantify the extent to which conservatisms in the TSPA Model, individually and collectively, overestimate the total mean annual dose relative to the model projections of the PMA
- Confirm that, when propagated through the TSPA Model, the evaluated conservatisms are indeed conservative with respect to the total system performance measures (e.g., total mean annual dose)
- **The water balance model is a submodel in the PMA that addresses conservatisms in the treatment of water fluxes into a breached waste package**




TSPA Model

- **Assumptions made in the treatment of water fluxes**
 - **Breaches in the WP outer layer due to general corrosion provide no resistance to advective seepage flow**
 - **Water vapor condensation inside a WP is controlled by water sorption onto corrosion products**
 - **No water is consumed by corrosion reactions**



Source Term Water (Q) Fluxes

$$\frac{dQ}{dt} = \text{Advection} + \text{Diffusion} - \text{Reaction}$$



$$F_{in}^{adv} = f_{in}^{adv} Q_{drip}$$

$$f_{in}^{adv} = 1 - \int_{\pi/2}^0 (-\sin \theta_0)(\cos \theta_0)^2 d\theta_0$$

$$\lambda = \frac{6\pi R_{wp} \phi K_p^s}{h^3}$$

Advection

$$\frac{dQ}{dt} = \frac{D\phi^{5/3} A}{L} (\rho_{out} - \rho_{in})$$

Diffusion

$$\psi = \psi_e (s_w)^{-b} [1 - \alpha(T_{in} - T_0)](1 + \beta m)$$


$$+ \omega \eta m \rho_{water} RT_{in}$$

$$RH_{in} = \frac{\rho_{in}}{\rho_s(T_{in})} = e^{-\frac{\psi \nu_w^0}{RT_{in}}}$$

H₂O Potential

$$F_{out}^{adv} = A_{out} K_c (s_w)$$

Advection



Reaction







Monte Carlo Analysis

- **Thermal inputs, dripping flux, and patch area boundary conditions**
- **Sample on degradation rates (steel, fuel, glass) hydrologic conductivity, dripping flux, rivulet thickness**
- **Calculate 30 realizations to predict water flux over 10,000 years**







Water Balance in the Package: Boundary Conditions and Results



00623PR_001.jpg







Water Balance in the Package: Predictions



00623PR_002.jpg





00623PR_003.jpg



Preliminary Results

- **Water saturations less than 0.5**
- **Advective outflows small (< 0.5 L/yr)**
- **Ionic strengths $> 1M$**

