



WIPP Lessons Learned from Experience in Operations and Heater Testing

**Nuclear Waste Technical Review Board
Albuquerque NM 19 March 2014**

**Abraham Van Luik, PhD
Carlsbad Field Office**



WIPP: A national solution



WIPP is currently the world's only operating deep geologic repository for permanent isolation of radioactive waste

Lessons Learned re: Disposal of Remote Handled Waste

- In-wall borehole disposal is not efficient
 - One canister is emplaced in an operation that takes ten to twelve hours from receipt to emplacement
 - Equipment size dictates excavation size
 - Slowness of emplacement operations and size of equipment blocks access to drift for contact-handled waste disposal purposes, causing boreholes to be passed over and go unused
- On the floor disposal in dedicated rooms enhances operational simplicity and efficiency



Remote Handled waste shipping casks are received in a horizontal position at WIPP



Rotation



Waste canisters pulled from shipping cask behind shield doors and placed into shielded facility cask for handling



Rotation

In the underground, the facility cask is removed from the hoist and transported to a disposal room by a 41-ton fork lift

Emplacement Experience at WIPP


Large, complex, heavy and hard to maintain equipment



RH waste in the canister is emplaced in pre-drilled boreholes in disposal room walls, and a concrete shield plug is inserted afterwards


RH & CH Waste Compete for Disposal Resources

All Remote Handled waste canisters and shield plugs must be inserted before Contact Handled waste emplacement can begin




Lessons Learned from WIPP


- Preferable to have a basic waste handling concept
 - Unload/transport shielded waste in single (horizontal) orientation
 - Eliminate RH placement in walls or vertically in floor
 - Emplace RH on floor unshielded, backfill with run-of-mine salt
 - Accept that “retrieval” of thermally hot and highly radioactive waste would be possible, but difficult
- Basic mining approach
 - Minimal mining
 - ◆ Single pass when possible
 - ◆ Angled entries
 - ◆ Narrow disposal rooms
 - Minimum roof support
 - ◆ Just-in-time mining
 - ◆ Maintain mains
 - Mine and emplace in same portion of repository



In-Drift Emplacement Concept



Emplacement and Closure Concept




Emplacement concept adapted from Carter, J.T., et al. (2012). "Reduced Backfilling and Backfilling." *Defense Waste Salt Repository Study*. DOE Office of Nuclear Energy Report ORNL/D-2012-000116.

Click on
the screen
to start
animation

**Small single-pass
mining with low
back to maximize
stand-up time**

**RH canisters
emplaced by
ROV and Run-
Of-Mine Salt For
Shielding**



**In-Drift, On-Floor
Emplacement
Concept in
Dedicated RH-
Only Panel**



Experience Leads to Further Design Optimization Insights



- Example design insight from WIPP experience
 - It may be useful to perform an engineering trade study on retreat emplacement on a whole-repository basis rather than just a panel basis, as done currently
 - Mains shorten with time
 - Panels can be permanently sealed as they are filled
 - But . . .
 - Initial extent of excavations may be a larger early investment
 - Flexibility for future expansion or major design changes may be reduced



Lesson Learned re: Past “Generic” Heater Tests

- In-floor borehole disposal invokes processes that can be mitigated
 - Sets up steep and very localized temperature and pressure gradients
 - Promotes migration of brine down pressure gradients
- In-floor borehole disposal for large, heavy packages is physically difficult and inefficient
 - Determines height and width of disposal rooms
 - Requires heavy, complex, shielded equipment to set containers upright and lower them into holes

1987



WIPP: surrogate for RW's Deaf Smith County site for high-level waste & used nuclear fuel

- Vertical borehole emplacement
- 18 W/m^2
- Coupons, brine, temperature monitored
- Peak temperatures never reached
- Tests terminated abruptly
- Limited post-test forensic examinations completed

1980's heater tests in WIPP focused on vertical borehole in-floor emplacement concept


Ventilation Air Flow



Through Open Drift



Disturbed Rock Zone



Formation pressure drives brine towards higher porosity

whether temperature gradient or not

Intact Salt

Intact Salt

Conclusions

- WIPP experience has two components:
 - Emplacement of remote handled waste in horizontal boreholes yielded direct insight into a potentially more efficient, simpler, and intrinsically safe emplacement scheme
 - Past experimental work has yielded insights into processes stimulated by high heat and pressure gradients, and how these gradients can be reduced
- Both experiences suggest that hot, higher radioactivity wastes can be disposed of safely and efficiently on a drift floor with run-of-mine salt and worker distance as shielding